



## THIN SUSPENSION

### SPECIFICATIONS

**Color / Finish**  
Black Oxide  
**Lens Finish**  
Frosted

**Segment Length**  
36 in [91.4 cm]  
**Power Supply**  
L. Standard Local 120-277V |  
2-Wire/TRIAC/Forward-Phase, 0-10V,  
ELV/Reverse-Phase

**Connected Sections**  
3 Connected Sections  
**Power Feed Location**  
Center Power Feed  
(Optional for 2+  
Connected Sections)

**Mounting**  
Direct-Mount to Ceiling  
**Canopy**  
2" Mini Canopy - Remote  
Power, Direct-Mount to  
Ceiling Only

**Color Temperature**  
3500K

## MORE INFORMATION & OPTIONS

---

### LIGHT QUALITY

0 CRI 95+, R9 90+ 32.00125

### LED LIFESPAN

1 50,000 hrs, L80 32.00125

### BODY MATERIAL

2 Solid Brass, PMMA  
32.00125

### CERTIFICATIONS

3 cUL, UL, CE, Damp  
Location Rated, Title 24  
32.00125

### DESIGNER

4 Peter Bristol 32.00125

### WATTAGE & LUMENS (PER SEGMENT)

5 24 IN – 6.8W, 0-600LM  
36 IN – 9.6W, 0-920LM  
47.50125

### WEIGHT

6 24 IN – 0.7 lbs  
36 IN – 0.85 lbs 44.50125

### MOUNTING

7 10ft 1/16" aircraft cable,  
field adjustable  
16ft Clear-jacketed 22AWG  
co-axial silver cord, field  
adjustable 44.50125